



CANILO

Suspended luminaires

CANILO is characterized by a classic, elegant design and offers a special element to support the customer CI: The side flap can be customized in color. The recessed reflector with integrated glare ring offers a high level of visual comfort. The variable and tool-free adjustable suspension in the form of a current-carrying cable gives it an elegant look.



Individual style

Side flap can be color-matched to customer CI



Uniform effect

The suspension and bracket specify the mounting direction and ensure a calm overall appearance if there are several luminaires.




Various mounting options

A ceiling canopy, a ceiling round or an adapter for attaching to conductor rails are available for mounting



High visual comfort

Recessed reflector ensures good glare control with no loss of light



CANILO

www.oktalite.com/canilo

Luminaire type	Suspended luminaires
Application areas	Accent lighting
Range of action	rigid
Fastening	3P conductor rail, structure, installation
Ceiling thickness	1 - 25 mm
Pendulum length	1500 mm, 3000 mm
Lighting technology	LED, LED IQ DALI, LED IQ BLE
Beam angel	Spot, Medium Flood, Flood, Wide Flood, Very Wide Flood
LED luminous flux class	2000 lm - 3000 lm
Light colour CRI 80	2700 K, 3000 K, 3500 K
Light colour CRI 90	3100 K - Brilliant Color, 3200 K - Efficient White, 4000 K - Efficient Cool
Supply unit	Integrated driver
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Weight	approx. 2.0
Test mark	