



KALO

TRACK LIGHTS

Small, efficient, unmistakable: the LED spotlight adapts easily to its area of use. The partly visible cooling fins enhance the plain white design. The ideal all-rounder for all applications.



Manageable size

Also suitable for low-ceilinged rooms or small rooms



Balanced center of gravity

Suspended power track remains balanced during swivelling-out of the spotlights



Customized illumination of the goods

Replacement of five interchangeable reflectors SP, MF, FL, WFL and VFL





Large selection of LEDs

Six white light colours and three special light colours for the fresh food area are available to choose from



Intelligent light

Smart lighting management optionally with control line or wireless



KALO

www.oktalite.com/kalo

Luminaire type	Track lights
Application areas	Accent lighting
Range of action	Can be rotated through 355° and swiveled through 180°
Fastening	3P conductor rail, not suitable for vertical mounting
Lighting technology	LED, LED IQ DALI, LED IQ BLE
Beam angle	Spot, Medium Flood, Flood, Wide Flood, Very Wide Flood
LED luminous flux class	1500 lm - 5000 lm
Light colour CRI 80	2700 K, 3000 K, 3500 K, 4000 K
Light colour CRI 90	3100 K - Brilliant Colour, 3200 K - Efficient White, 4000 K - Efficient Cool
Light colour Food	2700 K - Brilliant Food, Meat, Meat + Fish
Supply unit	Integrated driver
Luminaire colour	RAL 9005 jet black
	RAL 9006 white aluminum
	RAL 9016 traffic white
	Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Weight	approx. 1.2 kg
Test mark	