



LENTY MINI

TRACK LIGHTS

Small but powerful: LENTY MINI completes the LENTY spotlight family. The miniaturized lens technology performs as focused as the big ones: Even with small lumen packages, the brighter core light sets brilliant accents wherever the focus is on a discreet appearance. For example, in multi-space offices, in smaller sales rooms or with lower ceiling heights.



Lens technology instead of reflector technology

More concentrated and directed light on the target surface



Set highlights

High light intensity at 500 or 1000 lm; Beam angle from spot, medium flood to flood



For all light colours CRI > 90

Authentic lighting with Brilliant Colour or Efficient White, among others




Compatible for store, office, architecture

Multifunctional in white or black, front ring in white and black






Intelligent light

LED^{IQ} for your smart lighting management; controls from switchable, DALI, Bluetooth to BLE



LENTY MINI

www.oktalite.com/lenty-mini

| | |
|-------------------------|---|
| Luminaire type | Track lights |
| Application areas | Accent lighting in offices and retail |
| Range of action | Can be rotated through 355° and swiveled through 100 |
| Fastening | 3P conductor rail, not suitable for vertical mounting |
| Lighting technology | LED, LED IQ DALI, LED IQ BLE |
| Beam angle | Spot, Medium Flood, Flood, Wide Flood, Very Wide Flood |
| LED luminous flux class | 500 lm - 1000 lm |
| Light colour CRI 80 | 3000 K, 4000 K |
| Light colour CRI 90 | 2700 K, 3000 K, 3500 K, 4000 K – Efficient Cool |
| Supply unit | Track Driver 3PTD Invisible Driver 3PID (Coming soon) |
| Luminaire colour | RAL 9005 jet black RAL 9016 traffic white Special colours on request |
| Surface | Structure powder-coated, polycarbonate (PC) |
| Nominal voltage | 220 - 240 V, 50/60Hz |
| Weight | approx. 0.28 kg |
| Test mark |    |

